

	Pro	Pro-S	Titan	Titan-S	Elite	Elite-S	Pro-G Lith	PGT	Uno	Duo
Sizes when loading										
Min Overall Length when loading (mm)	1270	1270	1310	1310	1310	1310	1620	814	1710	2310
Min Overall Height when loading (mm)	520	680	560	690	510	690	620	940	1630	1890
Min Overall Width when loading (mm)	720	720	840	840	840	840	910	857	880	1240
Overall Tallest Part when built (mm)	1130	1105	1070	1070	1070	1070	1110	1145	1630	1760
Overall Weight inc battery (kg)	74	75	79	80	86	88	125	75	145	440
Sizes when Dismantled										
Heaviest part (Kg) when split	33	33	33	33	34	35	N/a	40	N/a	N/a
Longest part (mm)	770	770	770	770	770	770	1620	1618	N/a	N/a
Widest part (mm)	720	720	840	840	840	840	620	620	880	1240
Tallest Part (mm)	595	685	550	690	550	690	560	560	1630	1760
Splits into number of parts(Major)	5	5	5	5	5	5	2	2	N/a	N/a
General Spec										
Max Forward Speed (Km/h)	12	12	14	14	15	15	15	20	15	23
Max Reverse Speed (Km/h)	8	8	10	10	10	10	10	15	10	15
Ave. Dist. per Charge (Yards)	0-4500	0-4500*	12000*	12000*	12000*	12000*	18000	7500	15000	25000
^Max Weight of User for frame (Kg)	88	88	104	104	114	114	120	95	130	160
Tyres	Rubber Tube	Rubber Tube	Tubeless	Tubeless	Tubeless	Tubeless	Tubeless	Tubeless	Tubeless	Tubeless
Tyre Size (")	12 x 5	12 x 5	13 x 6.5	13 x 6.5	13 x 6.5	13 x 6.5	13 x 6.5	21 x 7x10	13 x 6.5	18 x 8.5
Turning Circle (Mtr)	3.7	3.7	4.5	4.5	4.5	4.5	4.5	1m	4.0	3.1
Gearbox Type	Transaxle	Transaxle	Transaxle	Transaxle	Transaxle	Transaxle	Transaxle	N/a	Transaxle	Transaxle
Engine size (cc) or Motor (W)	1000w	1000w	1000w	1000w	1000w	1000w	1200w	N/a	1200w	2400kw
Brake E=Electromagnetic	E	E	E	E	E	E	E	E	Gyro	E+Foot
Speed operated by	Hand	Foot	Hand	Foot	Hand	Foot	Hand/Twist	Movement	Foot	Foot
Dismantle	Yes	Yes	Yes	Yes	Yes	Yes	N/a	Partial	N/a	N/a
Mudguards inc.	No	No	No	No	Yes	Yes	Std	Std	N/a	N/a
Umbrella Holder inc.	No	No	No	No	Yes	Yes	Yes	No	N/a	Na
32" Bag Stand inc.	No	No	No	No	Yes	Yes	N/a	Inc	N/a	N/a
Luxury Bucket Seat inc.	No	No	No	No	Yes	Yes	Kab Sprung	N/a	N/a	N/a
Electrical System (Volt)	24	24	24	24	24	24	24	48v	36	48
Controller Make	Curtis	Curtis	Curtis	Curtis	S-Drive	S-Drive	S-Drive	Powerhouse	Curtis	Curtis
Controller Output (A)	100	100	110	110	140	140	180	N/a	160	400
Number of batteries	1	1	1	1	1	1	1	2	3	6
Battery Type**	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lead Acid DD
Battery Brand	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Powerhouse	Trojan
Battery Capacity (Ah)	22 (100A)	22 (100A)	30 (200A)	30 (200A)	30 (200A)	30 (200A)	47 (200A)	45 (200A)	45	165
Battery Weight (Kg Each)	5	5	7.5	7.5	7.5	7.5	14	6	26	28
Charging Time (hrs)	4-5	4-5	7-10	7-10	10	10	N/a	4	14-16	18-24
Battery Guarantee	12 Months	12 Months	24 Months	24 Months	24 Months	24 Months	24 Months	12 Months	24 Months	18 Months
Charger Output (Volts)	24	24	24	24	24	24	24	48	36	48
Charger Output (A)	6	6	6	6	9	9	12	12	12	25
Type of Charger	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Onboard	Intelligent	Intelligent
Climb Gradient (Degrees)	15-18	15-18	18-20	18-20	25-30	25-30	25-30	25-30	25-30	20-30
Recommended usage	Moderate	Moderate	Hard	Hard	Heavy	Heavy	Heavy	Heavy	Heavy	Semi Pro
Vat Exempt (if applicable)	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No
Recommended service schedule	Annually	Annually	Annually	Annually	Annually	Annually	Annually	Annually	Annually	Annually

Specification applicable from Jan 2017

Depending on terrain and conditions. DD= Deep Discharge Recovery. Please note many "Upgrades" not listed above are available. Please ask for details. ^This is the Maximum recommended weight of the user, for the frame. It is also assuming Lithium batteries are being used where applicable. Modifications to frame are available if needed. If in doubt, we recommend you contact us. The user must be aware of the "user weight limit" of the buggy. *Upgrade available. The Company can take no responsibility, if these limits are ignored and injury follows as a result. Telephone 0161 654 6981 email: Sales@powerhousegolf.co.uk Web: www.powerhousegolf.co.uk

